

چاپگر لیبل مدل Delta GA-۳۴۰۶T - Delta GA-۲۴۰۸T



Site: [www.rkara.ir](http://www.rkara.ir)

WhatsApp: ۰۹۳۹۲۲۲۰۶۱۳

Instageram: Rayaneh\_kara

Tell: ۰۳۱۳۲۶۶۶۲۷۷

Level	Standard
Resolution	GA-240AT: 6 dots/mm (240DPI) GA-240T: 12 dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal
Max. print speed	GA-240AT: 2.3mm(1")/second GA-240T: 1.5mm(1")/second
Max. print width	GA-240AT: 1.4 mm (0.9") GA-240T: 1.6.7 mm (0.6")
Max. print length	GA-240AT: 20,400 mm (1,000") GA-240T: 11,430 mm (0.45")
CPU	400 MHz, 32 bits, ARM9
Memory RAM	128 MB SDRAM
Memory ROM	128 MB Flash
Interface	<ul style="list-style-type: none"> <li>• USB 2.0 High Speed 480Mbps</li> <li>• USB Host 2.0, for scanner or PC keyboard</li> <li>• Ethernet 10/100Mbps</li> <li>• RS-232</li> <li>• Internal Bluetooth 2.0 (factory option)</li> <li>• Internal Wi-Fi (factory option)</li> </ul>
Real Time Clock	Optional
Buzzer	Optional
Dealer options	<ul style="list-style-type: none"> <li>• Guillotine cutter</li> <li>• Guillotine cutter for Linerless thermal label</li> <li>• Peeler</li> </ul>
Sensors	<ul style="list-style-type: none"> <li>• Head open sensor</li> <li>• Ribbon out sensor</li> <li>• Reflective sensor (moveable)</li> <li>• Transmissive sensor (moveable)</li> </ul>
Power	External universal switching power supply Input: AC 100-240V, 2.0A, 50-60Hz. Output: DC 24V, 2.0A, 6.0W
User Interface	<ul style="list-style-type: none"> <li>• 1 power switch</li> <li>• 1 button (Feed)</li> <li>• 3 LEDs (Online, Error, Ribbon, Wi-Fi/Bluetooth, Communication status)</li> </ul>
Internal fonts	<ul style="list-style-type: none"> <li>• 6 alpha-numeric bitmap fonts</li> <li>• True type font engine (need to download scalable font file)</li> </ul>
1D Barcode	Code 11, Code 39, Code 93, UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF12, MSI Pleassy, PostCode, Telepen

2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix
Rotation	Font and barcode support 0, 90, 180, 270 degree rotation
Printer language	Compatible to TSPL, EPL, ZPL, ZPL II, DPL
Media type	Continuous, die-cut, black mark, fan-fold(outside wound), Linerless Label
Media width	20~118 mm (0.7" ~ 4.6")
Media thickness	0.6~0.204mm (2.36 ~ 1.0 mil)
Media core diameter	20.4 mm (1")
Label roll capacity	127 mm (5") OD
Label length	GA-240AT: 0 ~ 20,400 mm (0.2" ~ 1,000") GA-240T: 0 ~ 11,430 mm (0.2" ~ 450")
Physical dimension	280mm(L) x 190mm(W) x 198.5mm(H)
Net Weight	2.7kg
Enclosure	Clamshell with double-walled plastic
Ribbon	300 meters long, max. OD 67 mm, 1" core (ink coated outside)
Ribbon width	20~110mm (0.78"~4.3")
Safety regulation	FCC Class A, CE Class A, CCC, BIS, CB
Environment condition	Operation: 0 ~ 40°C, 20 ~ 80% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Environmental concern	Comply with RoHS, REACH, WEEE
Accessories	<ul style="list-style-type: none"> <li>• Driver and software CD</li> <li>• Quick start guide</li> <li>• USB cable</li> <li>• Power cord</li> <li>• 1" ribbon spindle x 2</li> <li>• External universal switching power supply</li> </ul>