

Main Features

- *Press the button open cover, easy loading.
- *2200mA rechargeable lithium battery, over a week standby time
- *Support auto sleep,energy saving
- *Wide variety of interface:USB+Bluetooth 4.0(standard),USB+two BT,USB+three BT,USB+wifi+ BT(optional)
- *Bluetooth supports BT3.0&BT4.0,supports connect with Andriod ans iOS system
- *Support to print a variety of bitmap, 1D, 2D, or code
- *Provide DLL, SDK, Demo application for free.



Performance	Baby 380A
Printing method	Direct thermal
Thermal Speed	80mm/sec (max)
Reliability TPH life	50km
Resolution	576dot/line
Printing width	76mm
Paper width	80mm
Roll diameter	φ≤50mm
Paper thickness	0.06~0.08mm
Power	DC7.4V, 2A rechargeable Li-ion battery
Battery	Lithium: 7.4VDC/1900mAH
Charging mode	DC 9V/1.5A Charging time 2.5-3.5 hours
Print parameters	Support to download the logo trademark
Printing chinese character	GB18030/BIG 5/Korean Character. ANK Character: FontA:12*24dot,FontB:9*17dot. Korean/Simplified,Traditional Chinese:24*24dot
Barcode mode	UPC-A/UPC-/EAN(JAN)13/EAN(JAN)8/CODE39/CODABAR/ITF/CODE93/CODE128/QR Code
Code page	PC437, Katakana, PC850, PC860, PC863, PC865, West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866, PC852, PC858, IranII, Latvian, Arabic, PT151,1251, PC747, Vietnam, Uygur, Thai
Emulation	Compatible with ESC/POS
Interface	USB+Bluetooth;USB+WIFI(Android, iOS, (Win9X/Win ME/Win2000/WinNT/WinXP, WinVista, Win7, Win8, Linux))
Buffer	Input buffer 4K bytes NV Flash 60K bytes
Printer Dimension	131(h)*107(w)*58mm(h)
Working temperature	Temperature: 5 ~ 45℃, Humidity: 20 ~ 80%
Storage Environment	Temperature: -40 ~ 55℃ , Humidity: 20 ~ 90%
Weight(including battery)	350g
Accessories	Battery, Power Charger, USB Cable, CD Driver/SDK, Paper-roll
	Option: vehicle charger