



# DELTA 380B

Mode	Label	Receipt
Print Method	Direction thermal	
Resolution	203dpi	
Print speed	60mm/s	60mm/s
Interface	USB/(USB+bluetooth)/(USB+WIFI)	
Print width	80mm(max.)	72mm(max.)
Maximum print length	200mm for each label	No limited
Memory	DRAM:128KB FLASH:128KB	NV FLASH:60KB
Printhead temp detect	Thermistor	
Paper sensor	Photoelectric sensor	
Code page	PC437/PC850/PC852/PC860/PC863/ PC865/WPC1250/WPC1252/WPC1243/ WPC1254/WestEurope/Greek/ Hebrew/EastEurope/Iran/IranII/ Latvian/Arabic/Vietnam/Uygur/ Thai/WPC1251/WPC1257/Cyrillic/ PC858/PC747/PC864/PC1001	PC437/Katakana/PC850/PC860/PC863/PC 865/WestEurope/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC 858/IranII/Latvian/Arabic/PT151, 1251 /PC747/WPC1257/Vietnan/PC864/PC1001/ Uygur/Hebrew/WPC1255/PC720/WPC1256/ WOC1257/Thai/PC437/Katakana/PC437/PC 858/PC852/PC860/PC861/PC863/PC865/PC 866/PC855/PC857/PC862/PC864/PC737/PC 851/PC869/PC928/PC772/PC774/PC874/ WPC1252/WPC1250/WPC1251/PC3840/PC 3841/PC3843/PC3844/PC3845/PC3846/PC 3847/PC3848/PC1001/PC2001/PC3001/PC 3002/PC3011/PC3012/PC3021/PC3041
Barcode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, UPCA, UPCA+2, UPCA+5, UPC-E, UPC-E+2, UPC-E+5, QRCode	UPC-A, UPCE, EAN (JAN) 13, EAN (JAN) 8, CODE39, CODEBAR, ITF, CODE93, CODE128, QRCode
Character set	GB18030,simplified,BIG5,korean,japanese,ANK Character	
Font size	Font1:1x1.5mm(8x12dot) Font2-8 simplified,traditional chinese: 3.0x3.0mm(24x24dot)	FontA:1.5x3.0mm(12x24dot), FontB:1.1x2.1mm(9x17dot), simplified,traditional chinese: 3.0x3.0mm(24x24dot)
Character enlargement and rotation	1-10 times enlargement in horizontal and vertical directions,rotation print (0°,90°,180°,270°)	
Graphic	Monochrome PCX and BMP graphics can be download in flash and dram	
Media types	Thermal roll-fed or label or with black mark	
Media width	45mm to 80mm(contain liner)	80mm
Paper diameter	50mm±0.5mm	
Paper output	at the top of printer,tear off	
Lithium Battery	7.4V 2200mAh	
Charge Time	3-5h	
Power adapter	Input : AC 220V output : DC 9V/1A	
Operation environment	Temperature:5~45°C humidity:≤93%RH(no-condensation)	
Storage environment	Temperature:5~45°C humidity:≤93%RH(no-condensation)	
Dimension	131x107x58mm(LxWxH)	
Weight	360G	
Driver compatible	Win9X/WinME/Win2000/WinNT/WinXP, WinVista, Win7, Win8, Win10, Linux	
Setting tools	GpTools(Android)、GprinterSetTool(Windows)	