



## Delta 7270

Scan mode Omni directional 2D Image scanning

Alarm mode LED light alarm, Buzzer alarm

Scan rate 2100times/sec

Scan depth of field 4mil(Code 39) 20~120mm

13mil(UPC/EAN) 20~210mm

15mil(PDF417) 20~180mm

15mil(QR code) 30~130mm

Reading Angle Horizontal  $\pm 55^\circ$ , Vertical  $\pm 37.5^\circ$

Resolution SXGA-W(Width1280\*Height\*1024) Ratio (5 : 4)

Barcode type Australian Post, Aztec, BPO, Canada Post, Codabar, Codablock, Code 11, Code 39, Code 93, Code 128/EAN128, DataMatrix, Dutch Post, EAN.UCC Composite, Interleaved 2 of 5, Japan Post, Matrix 2 of 5, MaxiCode, MicroPDF417, MSI Code, PDF417, Planet, Plessey Code, Postnet, QR code, RSS, Standard 2 of 5, Telepen, TLC 39, UPC/EAN.....

### Electrical

Voltage DC+5V $\pm 5\%$  or +3.3V $\pm 5\%$

Current: 200mA(stand by);420mA(operation)

Interfaces USB (Drive Free) ,USB Virtual RS232(Install Drive), RS232(Drive Free)

Current consumption  $\pm 10\%$

Light level Wavelength:675nm $\pm 3$ nm Infrared LED

### Environmental

Operating temperature  $-20^\circ\text{C} \sim 60^\circ\text{C}$

Storage temperature  $-40^\circ\text{C} \sim 70^\circ\text{C}$

Humidity 5% to 95% (Non-condensing)

Drop Designed to withstand 1.2m drops

### Physical

Dimensions (LxWxH) 110MM\*124MM\*152MM

Weight 450g