

Delta T60 — 80 mm Thermal Receipt Printer



Model	Delta T60	
Print Method	Direct thermal	
Print Speed	180mm/s	
Paper Width	79.5±0.5mm	
Print Width	64/72mm	
Interface	Ethernet/Serial+USB	
Power	DC 24V/2.5A	
Reliability(Mechanism)	150km	
Weight	0.95KG	
Dimension	169×129×130 (W×D×H)	
Columns	Font A - 42columns or 48columns / Font B - 56columns or 64columns / Simplified/Traditional Chinese - 21columns or 24columns	
Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots Simplified/ Traditional Chinese: 24×24dots	
Code page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/ IranII /Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/ (PC864)/(Vietnam)/(Thai)	
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128/QRCODE/PDF417	
Data	128K bytes	
NV Flash	256K bytes	
Cash drawer out	DC 24V/1A	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/1.5A	
Work environment	Temperature: 0 ~ 45°C, Humidity: 10 ~ 80%	
Storage environment	Temperature: -10 ~ 60°C, Humidity: 10 ~ 90%	