

بارکدخوان ۲D ۷۲۰۰ Delta



Physical Characteristics

Deminsions : 137.40mm x 99.80mm x 96.50mm

Voltage : 5±5%V

Current : 235mA

Weight : 262.5g

Work Current: 315mA

Starting Current: 320mA

Performance Characteristics

Image (Pixels) : CMOS 840 pixels (H) x 640 pixels (V)

Light Source : (Aimer) Blue color LED; (Illumination) Red color LED

Field of View : 39°(H) X29°(V)

Roll / Pitch / Yaw : 360°(Roll), ±65°(Skew) , ±65°(Pitch)

Print Contrast : 20% minimum reflective difference

Interfaces Supported : USB

Motion Tolerances : >40cm/s

Symbology Decode Capability

1-D: Codabar, Code 39, Code 32 Pharmaceutical (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Straight 2 of 5 IATA ,Matrix 2 of 5 ,Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, China Post(Hong Kong 2 of 5), Korea Post

2-D: PDF417, QR code, MicroPDF417, Australian Post, Canada Post,Japan Post, MaxiCode, Codablock, Aztec, Dutch Post, DataMatrix, etc.

Minimum Resolution: ≥4mil

User Environment

Operating Temperature : -20°C to 60°C

Storage Temperature : -30°C to 70°C

Humidity : 5% to 95% relative humidity, non-condensing

Shock Specifications : Designed to withstand 1.2m(5') drops

Ambient Light Immunity : 0-100,000 Lux.

Decode Ranges

Code39(5mil) : 0-7cm

Code39(13mil) : 0-17cm

QR(20mil) : 0-11cm

Dimension:

