



Model No.	Delta T90
Print method	Direct thermal line
Dot density	512dot/line, 576dot/line
Print speed	300mm/s
Paper width	80±0.5mm
Print width	64/72mm
Interface	Serial+USB+Ethernet;Parallel+USB
Paper diameter	83mm
Line space	3.75mm(can be adjusted by sending commands)
Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128
Code page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151, 1251 /PC737/WPC1257/Thai Vietnam/PC864/PC1001/ (Latvian)/(PC1001)/ (PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Character	ANK Character Font A: 12×24dots Font B: 9×17dots Simplified/ Traditional Chinese: 24×24dots
Driver Supported	Windows 9X/ME/2000/2003/XP/Vista/7/8
Fonts	GB18030
Buffer Data:	128K bytes
NV Flash	256K bytes
Cash drawer out	DC 24V/1A
Power Supply	DC 24V/2A
Power adapter	Input: AC 110V/220V,50-60Hz Output:DC 24V/2A
Reliability	150km
Auto Cutter	1.5 million cuts
Weight	1.26KG
Dimension	136×190×130mm(W*L*H)
Work environment	Temperature: 0~45℃, Humidity: 10~80%
Storage environment	Temperature:-10~60℃, Humidity: 10~90%